

ENERG
енергия · ενεργεια
Y
IJA
IE
IA
Haier
AW082MUGHA
55 °C
35 °C
A+++
A++
A+
A
B
C
D
A+++
A+++
6.00
6.00
6.00
kW
7.50
7.20
7.50
kW
dB
64 dB
2019
811/2013

Haier

Model(s): [information identifying the model(s) to which the information relates]	AW082MUGHA
Air-to-water heat pump:	Yes
Water-to-water heat pump:	No
Brine-to-water heat pump:	No
Low-temperature heat pump:	No
Equipped with a supplementary heater:	No
Heat pump combination heater:	No
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.	Low-temperature application
Parameters shall be declared for average, colder and warmer climate conditions.	Average climate conditions

Item	symbol	Value	Unit	Item	symbol	Value	Unit
Rated heat output (*)	P_{rated}	7.2	kW	Seasonal space heating energy efficiency	η_s	205	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j= – 7 °C	P_{dh}	6.34	kW	T_j = – 7 °C	COP_d or PER_d	3.43	– or%
T_j = + 2 °C	P_{dh}	3.89	kW	T_j = + 2 °C	COP_d or PER_d	5.01	– or%
T_j = + 7 °C	P_{dh}	2.52	kW	T_j = + 7 °C	COP_d or PER_d	6.88	– or%
T_j = + 12 °C	P_{dh}	3.56	kW	T_j = + 12 °C	COP_d or PER_d	8.83	– or%
T_j = bivalent temperature	P_{dh}	6.34	kW	T_j = bivalent temperature	COP_d or PER_d	3.43	– or%
T_j = operation limit temperature	P_{dh}	7.11	kW	T_j = operation limit temperature	COP_d or PER_d	2.34	– or%
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	N/A	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	N/A	– or%
Bivalent temperature	T_{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater: N/A			
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	0.09	kW
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input		-	
Standby mode	P_{SB}	0.018	kW				
Crankcase heater mode	P_{CK}	0	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3028	m^3/h
Sound power level, indoors/ outdoors	L_{WA}	-/59	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	1.376	m^3/h
Annual energy consumption	Q_{HE}	2866	kWhor GJ				
For heat pump combination heater: N/A							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.

0150570940

Model(s): [information identifying the model(s) to which the information relates]	AW082MUGHA
Air-to-water heat pump:	Yes
Water-to-water heat pump:	No
Brine-to-water heat pump:	No
Low-temperature heat pump:	No
Equipped with a supplementary heater:	No
Heat pump combination heater:	No
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.	Medium-temperature application
Parameters shall be declared for average, colder and warmer climate conditions.	Average climate conditions

Item	symbol	Value	Unit	Item	symbol	Value	Unit
Rated heat output (*)	P_{rated}	6	kW	Seasonal space heating energy efficiency	η_s	151	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j= – 7 °C	P_{dh}	5.28	kW	T_j = – 7 °C	COP_d or PER_d	2.48	– or%
T_j = + 2 °C	P_{dh}	3.24	kW	T_j = + 2 °C	COP_d or PER_d	3.65	– or%
T_j = + 7 °C	P_{dh}	2.10	kW	T_j = + 7 °C	COP_d or PER_d	5.43	– or%
T_j = + 12 °C	P_{dh}	3.22	kW	T_j = + 12 °C	COP_d or PER_d	6.70	– or%
T_j = bivalent temperature	P_{dh}	5.28	kW	T_j = bivalent temperature	COP_d or PER_d	2.48	– or%
T_j = operation limit temperature	P_{dh}	5.95	kW	T_j = operation limit temperature	COP_d or PER_d	1.85	– or%
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	N/A	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	N/A	– or%
Bivalent temperature	T_{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater: N/A			
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	0.05	kW
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input		-	
Standby mode	P_{SB}	0.018	kW				
Crankcase heater mode	P_{CK}	0	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3429	m^3/h
Sound power level, indoors/ outdoors	L_{WA}	-/64	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	0.860	m^3/h
Annual energy consumption	Q_{HE}	3223	kWhor GJ				
For heat pump combination heater: N/A							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.

0150570940

Model(s): [information identifying the model(s) to which the information relates]				AW082MUGHA				
Air-to-water heat pump:				Yes				
Water-to-water heat pump:				No				
Brine-to-water heat pump:				No				
Low-temperature heat pump:				No				
Equipped with a supplementary heater:				No				
Heat pump combination heater:				No				
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.				Low-temperature application				
Parameters shall be declared for average, colder and warmer climate conditions.				Cold climate conditions				
Item	symbol	Value	Unit	Item	symbol	Value	Unit	
Rated heat output (*)	P_{rated}	7.5	kW	Seasonal space heating energy efficiency	η_s	163	%	
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j				
T_j= – 7 °C	P_{dh}	5.47	kW	T_j = – 7 °C	COP_d or PER_d	3.55	– or%	
T_j = + 2 °C	P_{dh}	3.44	kW	T_j = + 2 °C	COP_d or PER_d	5.00	– or%	
T_j = + 7 °C	P_{dh}	4.15	kW	T_j = + 7 °C	COP_d or PER_d	6.85	– or%	
T_j = + 12 °C	P_{dh}	5.03	kW	T_j = + 12 °C	COP_d or PER_d	9.23	– or%	
T_j = bivalent temperature	P_{dh}	7.38	kW	T_j = bivalent temperature	COP_d or PER_d	2.46	– or%	
T_j = operation limit temperature	P_{dh}	5.75	kW	T_j = operation limit temperature	COP_d or PER_d	1.85	– or%	
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	7.4	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	2.5	– or%	
Bivalent temperature	T_{biv}	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C	
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%	
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	60	°C	
Power consumption in modes other than active mode				Supplementary heater: N/A				
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	1.75	kW	
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input	-			
Standby mode	P_{SB}	0.018	kW					
Crankcase heater mode	P_{CK}	0	kW					
Other items								
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3028	m^3/h	
Sound power level, indoors/ outdoors	L_{WA}	-/59	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	1.376	m^3/h	
Annual energy consumption	Q_{HE}	3430	kWhor GJ					
For heat pump combination heater: N/A								
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%	
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh	
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ	
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China							
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.								

0150570940

Model(s): [information identifying the model(s) to which the information relates]			AW082MUGHA				
Air-to-water heat pump:			Yes				
Water-to-water heat pump:			No				
Brine-to-water heat pump:			No				
Low-temperature heat pump:			No				
Equipped with a supplementary heater:			No				
Heat pump combination heater:			No				
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.			Medium-temperature application				
Parameters shall be declared for average, colder and warmer climate conditions.			Cold climate conditions				
Item	symbol	Value	Unit	Item	symbol	Value	Unit
Rated heat output (*)	P_{rated}	6	kW	Seasonal space heating energy efficiency	η_s	126	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j= – 7 °C	P_{dh}	4.29	kW	T_j = – 7 °C	COP_d or PER_d	2.83	– or%
T_j = + 2 °C	P_{dh}	3.20	kW	T_j = + 2 °C	COP_d or PER_d	3.76	– or%
T_j = + 7 °C	P_{dh}	4.05	kW	T_j = + 7 °C	COP_d or PER_d	5.52	– or%
T_j = + 12 °C	P_{dh}	4.84	kW	T_j = + 12 °C	COP_d or PER_d	8.03	– or%
T_j = bivalent temperature	P_{dh}	5.76	kW	T_j = bivalent temperature	COP_d or PER_d	2.13	– or%
T_j = operation limit temperature	P_{dh}	4.40	kW	T_j = operation limit temperature	COP_d or PER_d	1.58	– or%
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	5.8	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	2.1	– or%
Bivalent temperature	T_{biv}	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater: N/A			
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	1.60	kW
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input		-	
Standby mode	P_{SB}	0.018	kW				
Crankcase heater mode	P_{CK}	0	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3429	m^3/h
Sound power level, indoors/ outdoors	L_{WA}	-/64	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	0.860	m^3/h
Annual energy consumption	Q_{HE}	3381	kWhor GJ				
For heat pump combination heater: N/A							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.							

0150570940

Model(s): [information identifying the model(s) to which the information relates]	AW082MUGHA
Air-to-water heat pump:	Yes
Water-to-water heat pump:	No
Brine-to-water heat pump:	No
Low-temperature heat pump:	No
Equipped with a supplementary heater:	No
Heat pump combination heater:	No
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.	Low-temperature application
Parameters shall be declared for average, colder and warmer climate conditions.	Warm climate conditions

Item	symbol	Value	Unit	Item	symbol	Value	Unit
Rated heat output (*)	P_{rated}	7.5	kW	Seasonal space heating energy efficiency	η_s	258	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j= – 7 °C	P_{dh}	/	kW	T_j = – 7 °C	COP_d or PER_d	/	– or%
T_j = + 2 °C	P_{dh}	9.09	kW	T_j = + 2 °C	COP_d or PER_d	4.11	– or%
T_j = + 7 °C	P_{dh}	5.83	kW	T_j = + 7 °C	COP_d or PER_d	6.12	– or%
T_j = + 12 °C	P_{dh}	4.99	kW	T_j = + 12 °C	COP_d or PER_d	8.57	– or%
T_j = bivalent temperature	P_{dh}	9.09	kW	T_j = bivalent temperature	COP_d or PER_d	4.11	– or%
T_j = operation limit temperature	P_{dh}	9.09	kW	T_j = operation limit temperature	COP_d or PER_d	4.11	– or%
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	N/A	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	N/A	– or%
Bivalent temperature	T_{biv}	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater: N/A			
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	-	kW
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input	-		
Standby mode	P_{SB}	0.018	kW				
Crankcase heater mode	P_{CK}	0	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3028	m^3/h
Sound power level, indoors/ outdoors	L_{WA}	-/59	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	1.376	m^3/h
Annual energy consumption	Q_{HE}	1579	kWhor GJ				
For heat pump combination heater: N/A							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.

Model(s): [information identifying the model(s) to which the information relates]	AW082MUGHA
Air-to-water heat pump:	Yes
Water-to-water heat pump:	No
Brine-to-water heat pump:	No
Low-temperature heat pump:	No
Equipped with a supplementary heater:	No
Heat pump combination heater:	No
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.	Medium-temperature application
Parameters shall be declared for average, colder and warmer climate conditions.	Warm climate conditions

Item	symbol	Value	Unit	Item	symbol	Value	Unit
Rated heat output (*)	P_{rated}	6	kW	Seasonal space heating energy efficiency	η_s	185	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
T_j= – 7 °C	P_{dh}	/	kW	T_j = – 7 °C	COP_d or PER_d	/	– or%
T_j = + 2 °C	P_{dh}	6.97	kW	T_j = + 2 °C	COP_d or PER_d	2.83	– or%
T_j = + 7 °C	P_{dh}	4.42	kW	T_j = + 7 °C	COP_d or PER_d	4.24	– or%
T_j = + 12 °C	P_{dh}	4.72	kW	T_j = + 12 °C	COP_d or PER_d	6.68	– or%
T_j = bivalent temperature	P_{dh}	6.97	kW	T_j = bivalent temperature	COP_d or PER_d	2.83	– or%
T_j = operation limit temperature	P_{dh}	6.97	kW	T_j = operation limit temperature	COP_d or PER_d	2.83	– or%
For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	P_{dh}	N/A	kW	For air-to-water heat pumps: T_j = – 15 °C (if TOL < – 20 °C)	COP_d or PER_d	N/A	– or%
Bivalent temperature	T_{biv}	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-25	°C
Cycling interval capacity for heating	P_{cych}	N/A	kW	Cycling interval efficiency	COP_d or PER_d	0.9	– or%
Degradation co- efficient (**)	C_{dh}	0.9	—	Heating water operating limit temperature	WTOL	80	°C
Power consumption in modes other than active mode				Supplementary heater: N/A			
Off mode	P_{OFF}	0.018	kW	Rated heat output (*)	P_{sup}	-	kW
Thermostat-off mode	P_{TO}	0.018	kW	Type of energy input	-		
Standby mode	P_{SB}	0.018	kW				
Crankcase heater mode	P_{CK}	0	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	—	3429	m^3/h
Sound power level, indoors/ outdoors	L_{WA}	-/64	dB(A)	For water- or brine-to- water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	N/A	0.860	m^3/h
Annual energy consumption	Q_{HE}	1675	kWhor GJ				
For heat pump combination heater: N/A							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q_{elec}	-	kWh	Daily fuel consumption	Q_{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	Qingdao Haier Air Conditioner Electric Co., Ltd. Haier industrial Park,No.236,Qianwangang Road ,Qingdao Eco-tech Development Zone ,Qingdao , 266555,China						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater P_{sup} is equal to the supplementary capacity for heating sup(T_j). (**) If C_{dh} is not determined by measurement then the default degradation coefficient is C_{dh} = 0,9.